










▶ Transient Voltage Suppressors (TVS)

Package Types	Part No.	Electrical Characteristics(Rating at 25°C Ambient Temperature)				
		Peak Power Dissipation PPK(W)	Reverse Standoff Voltage-Vwm(V)	Max.Peak Pulse Current-Ipp(A)	Max. Clamping Voltage Vc (V)@Ipp	Max.Reverse Leakage ID(uA)@Vwm
 SOD-123FL	SMF5.0(C)A~SMF170(C)A	200	5.0~170	21.7~0.6	9.2~275	400~1.0
	SM4F5.0A~SM4F170A	400	5.0~170	43.5~1.5	9.2~275	800~1.0
 DO-221AC	SMA6F5.0A~SMA6F13A	600	5~13	68~29	9.2~20.4	800~5.0
 DO-218AB	SM5S14A~SM5S36A *	3600	14~36	155~62	23.2~58.1	10
	SM6S10A~SM6S43A *NEW*	4600	10~43	271~66	17~69.4	15~10
	SM8S14A~SM8S43A *	6600	14~43	284~95.1	23.2~69.4	10
 SMA(DO-214AC)	SMAJ5.0(C)(A)~SMAJ440(C)(A)	400	5~440	43.5~0.6	9.2~713	800~1.0
	SMAJP4KE6.8(C)(A)~SMAJP4KE550(C)(A)	400	5.8~495	39~0.5	10.5~760	1000~1
	SMA6J5.0(C)(A)~SMA6J40(C)(A)	600	5~40	65.2~9.3	9.2~64.5	800~1.0
	SMAJ10(C)AHE3~SMAJ85(C)AHE3 *	400	10~85	23.5~2.9	17~137	5.0~1.0
	SMAJP4KE12(C)AHE3~SMAJP4KE100(C)AHE3 *	400	10.2~85.5	24.6~3.0	16.7~137	5.0~1.0
 SMB(DO-214AA)	SMBSAC5.0~SMBSAC50	500	5~50	44~5.8	10~88	300~5.0
	SMBJP6KE6.8(C)(A)~SMBJP6KE550(C)(A)	600	5.8~495	58.1~0.8	10.5~760	1000~1.0
	SMBJ5.0(C)(A)~SMBJ440(C)(A)	600	5~440	65.2~0.9	9.2~713	800~1.0
	SMBJ11(C)AHE3~SMBJ78(C)AHE3 *	600	11~78	33.0~4.7	18.2~126.0	5.0
	SMBJP6KE13(C)AHE3~SMBJP6KE91(C)AHE3 *	600	11.1~77.8	33.5~4.9	18.2~125.0	1.0
	SMB10J5.0(C)A~SMB10J58(C)A	1000	5.0~58.0	108.7~10.68	9.2~93.6	800~1.0
 SMC(DO-214AB)	SMCJ5.0(C)(A)~SMCJ440(C)(A)	1500	5~440	163~2.1	9.2~713	800~5.0
	SMCJ1.5KE6.8(C)(A)~SMCJ1.5KE550(C)(A)	1500	5.8~495	144.8~2	10.5~760	1000~5.0
	SMLJ5.0(C)(A)~SMLJ440(C)(A)	3000	5~440	312.5~4.21	9.2~713	1000~2.0

* Automotive Grade TVS

▶ Transient Voltage Suppressors (TVS)

Package Types	Part No.	Electrical Characteristics(Rating at 25°C Ambient Temperature)				
		Peak Power Dissipation PPK(W)	Reverse Standoff Voltage-Vwm(V)	Max.Peak Pulse Current-Ipp(A)	Max. Clamping Voltage Vc (V)@Ipp	Max.Reverse Leakage ID(uA)@Vwm
 SMC(DO-214AB)	5.0SMLJ11(C)(A)~5.0SMLJ400(C)(A)	5000	11~400	275~7.7	18.2~648	800~5.0
	SMCJ10(C)AHE3~SMCJ78(C)AHE3 *	1500	10~78	88.3~11.9	17~126	5.0~1.0
	SMCJ1.5KE12(C)AHE3~SMCJ1.5KE91(C)AHE3 *	1500	10.2~77.8	91~12.2	16.7~125	5.0~1.0
	SMLJ10(C)AHE3~SMLJ43(C)AHE3 *	3000	10~43	176.4~43.2	17~69.4	15~2.0
 DO-41	P4KE6.8(C)(A)~P4KE550(C)(A)	400	5.8~495	39~0.52	10.5~760	1000~1.0
 DO-15	P5KE5.0(C)(A)~P5KE200(C)(A)	500	5~200	52.3~1.5	9.2~324	600~3.0
	SAC5.0~SAC50	500	5~50	44~5.8	10~88	300~5.0
	SA5.0(C)(A)~SA170(C)(A)	500	5~170	55.4~1.9	9.2~275	600~1.0
	P6KE6.8(C)(A)~P6KE600(C)(A)	600	5.5~512	57~0.75	10.5~828	1000~1.0
	SAC136	...	136	2.7	219	1.0
 DO-201AE	1.5KE6.8(C)(A)~1.5KE550(C)(A)	1500	5.8~467	144.8~2	10.5~760	1000~5.0
	LCE6.5A~LCE28A	1500	6.5~28	100~33	11.2~45.5	1000~5.0
 R-6	3KP5.0(C)(A)~3KP220(C)(A)	3000	5~220	326.1~8.1	9.2~371.1	5000~10
	5KP5.0(C)(A)~5KP250(C)(A)	5000	5~250	543~12	9.2~425	5000~10
	15KP17(C)(A)~15KP280(C)(A)	15000	17~280	512~33	29.3~452	5000~10
	30KP28(C)(A)~30KP288(C)(A)	30000	28~288	606~64.5	50~469.9	5000~10
	SLD10(C)A~SLD60(C)A	6000	10~60	350~61.5	17~96.8	10
 AK	AK1-076C~AK15-076C	...	58~430	1K~15K	110~625	20

* Automotive Grade TVS