

Obsolete

M.C.C.

Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

NTG Series

Features

- DO-35 glass package
- High stability
- Wide range of operating temperature from -50°C up to 250°C
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Moisture Sensitivity: Level 1 per J-STD-020C

Applications

- Low cost probe assemblies
- High temperature printer ink sensing
- Consumer electronics
- High temperature – high speed tire manufacturing
- Printed circuit board temperature sensing
- Air-conditioner

General Characteristics


Symbol	Parameter	Value	Unit
R ₂₅	Rated zero-power resistance	10 ² ~10 ⁶	Ω
	Tolerance of R ₂₅	±1%, ±2%, ±3%, ±5%, ±10%	
B _{0/50} B _{25/50} B _{25/85}	Range of B value	2000~5000	K
	Tolerance of B value	±0.5%, ±1%, ±1.5%	
	Dissipation factor*	≥ 2.0	mW
	Thermal time constant*	≤ 20	Sec.
	Rated power	250	mW
	Operating temperature range	-50 ~ +250	°C

* In still air

Note: 1. Lead in Glass Exemption Applied, see EU Directive Annex 7(C)-I.

High Accuracy NTC Thermistors

DO-35 GLASS



DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	---	.166	---	4.2	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.000	---	25.40	---	

Temperature	NTG 502-32XX	NTG 502-34XX	NTG 103-35XX	NTG 103-33XX	NTG 103-39XX	NTG 403-35XX	NTG 503-40XX	NTG 104-36XX	NTG 104-41XX	Package
°C	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	
-50	154.5	208.6		329.2						DO-35G
-40	88.85	112.86	249.6	188.4						
-30	52.85	63.73	140.0	111.3	176.98					
-20	32.43	37.40	80.36	67.74	97.10					
-10	20.48	22.72	47.73	42.45	55.35					
0	13.29	14.23	29.37	27.28	32.67	115.0	167.1	301.3	340.9	
10	8.839	9.181	18.68	17.96	19.91	73.87	100.5	190.1	204.0	
20	6.013	6.086	12.24	12.09	12.50	48.77	62.61	123.1	125.9	
30	4.179	4.132	8.221	8.313	8.049	33.00	40.07	81.71	79.77	
40	2.962	2.869	5.648	5.828	5.314	22.82	26.28	55.40	51.82	
50	2.138	2.032	3.958	4.161	3.589	16.10	17.69	38.32	34.47	
60	1.568	1.467	2.823	3.021	2.478	11.57	12.13	27.01	23.42	
70	1.169	1.073	2.047	2.229	1.745	8.460	8.498	19.39	16.27	
80	0.8838	0.7959	1.506	1.669	1.252	6.281	6.051	14.15	11.52	
90	0.6774	0.5975	1.124	1.266	0.9117	4.732	4.390	10.49	8.305	
100	0.5267	0.4533	0.8502	0.9735	0.6739	3.613	3.226	7.870	6.092	
110	0.4130	0.3514	0.6510	0.7579	0.5064	2.793	2.409	5.971	4.524	
120	0.3276	0.2756	0.5046	0.5965	0.3858	2.183	1.821	4.583	3.411	
130	0.2631	0.2186	0.3956	0.4750	0.2974	1.728	1.395	3.553	2.603	
140	0.2131	0.1751	0.3137	0.3821	0.2321	1.379	1.081	2.784	2.008	
150	0.1742	0.1418	0.2515	0.3103	0.183	1.108	0.8473	2.202	1.569	
160						0.8948	0.6707	1.758	1.238	
170						0.7256	0.5364	1.417	0.9878	
180						0.5918	0.4331	1.151	0.7944	
190						0.4862		0.9423	0.6454	
200						0.4020		0.7774	0.5280	
210						0.3346		0.6452	0.4349	
220						0.2803		0.5406	0.3611	
230						0.2362		0.4553	0.3018	
240						0.2001		0.3857	0.2539	
250						0.1705		0.3288	0.2149	
260								0.2817	0.1831	
280										
300										
R ₂₅	5.00K	5.00K	10.00K	10.00K	10.00K	40.00K	50.00K	100.00K	100.00K	
B _{25/50}	3275	3470	3572	3380	3950	3508	4000	3697	4100	
B _{25/85}	3324	3528	3630	3435	3983	3550	4048	3750	4140	

Type No.

NTG XXX - XXXX X - X X
 ① ② ③ ④ ⑤ ⑥

- ① Series name
- ② Zero-power resistance(R_{25}), for example:
 502 ----- 5 K Ω
 503 ----- 50 K Ω
 104 ----- 100 K Ω
- ③ B value, for example:
 3850 ----- B value is 3850K
 3950 ----- B value is 3950K
- ④ Type of B value, for example:
 A ----- B_{0/50}
 B ----- B_{25/50}
 C ----- B_{25/85}
- ⑤ Tolerance of R_{25} , for example:
 1 ----- Tolerance of R_{25} is 1%
 5 ----- Tolerance of R_{25} is 5%
 0 ----- Tolerance of R_{25} is 10%
- ⑥ Tolerance of B value, for example:
 1 ----- Tolerance of B value is 1%
 2 ----- Tolerance of B value is 2%



TM

Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 10Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box
Part Number-BP	Bulk: 500Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com