



**Micro Commercial Components** 



Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# **DL4154**

## **Features**

- Fast Switching Speed and Low Current Leakage
- Compression Bond Construction and Low Cost
- Surface Mount Application
- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

## **Maximum Ratings**


- Operation & Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance: 400k/W Junction to Ambient

Electrical Characteristics @ 25°C Unless Otherwise Specified


Reverse Voltage	$V_R$	25V		
Peak Reverse Voltage	$V_{RM}$	35V		
Average Rectified Current	Io	150mA	Resistive Load f>50Hz	
Power Dissipation	P <sub>TOT</sub>	500mW		
Junction Temperature	$T_J$	175°C		
Maximum Instantaneous Forward Volt.	V <sub>F</sub>	1.0V	I <sub>FM</sub> =10mA; T <sub>J</sub> =25°C	
Maximum DC Reverse Current At Rated DC Blocking Volt.	I <sub>R</sub>	0.1µA	V <sub>R</sub> =25V T <sub>J</sub> =25°C	
Typical Junction Capacitance	CJ	4pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V	
Reverse Recovery Time	Trr	2nS	$I_F=10$ mA $V_R=6$ V $I_R=1$ mA $R_L=100$ OHMS	

Note: 1.Lead in Glass Exemption Applied, see EU Directive Annex 5.

# Small Signal Switching Diode




DIMENSION					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
Α	.130	.146	3.30	3.70	
В	.008	.016	.20	.40	
С	.055	.059	1.40	1.50	










T<sub>A</sub>, AMBIENT TEMPERATURE (°C) Fig. 1 Power Derating Curve



V<sub>F</sub>, FORWARD VOLTAGE (V) Fig. 2 Forward Characteristics





Fig. 3 Relative Capacitance Variation



T<sub>i</sub>, JUNCTION TEMPERATURE (°C) Fig. 4 Leakage Current vs Junction Temperature



#### **Micro Commercial Components**

### Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.