

	<b>E502650</b>
---	----------------


**Features**

- Glass Passivated Chip Junction
- High Surge Current Capability
- Lead Free Finish/RoHS Compliant (Note 1)("P" Suffix Designates RoHS Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating

**Maximum Ratings @ 25°C (Unless Otherwise Specified)**

Parameter	Symbol	Value	Unit
		SKBPC3516	
Peak Repetitive Reverse Voltage	$V_{RRM}$	1600	V
Working Peak Reverse Voltage	$V_{RWM}$		
DC Blocking Voltage	$V_R$		
RMS Reverse Voltage	$V_{RMS}$	1120	V
Average Rectified Forward Current @ $T_C=55^\circ C$	$I_{F(AV)}$	35	A
Non-Repetitive Peak Surge Current @ 8.3ms Half Sine Wave	$I_{FSM}$	425	A
$I^2t$ Rating for Fusing @ $1ms \leq t \leq 8.3ms$	$I^2t$	750	A <sup>2</sup> s
Dielectric strength @ Terminals to Case, AC 1 Minute	$V_{dis}$	2.5	KV



# 35 Amp Three Phase Bridge Rectifiers 1600 Volts



**SKBPC**

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.909	0.949	23.10	24.10	
B	0.909	0.949	23.10	24.10	
C	1.110	1.134	28.20	28.80	
D	0.630	0.669	16.00	17.00	
E	/	0.984	/	25.00	
F	0.425	0.441	10.80	11.20	
G	0.244	0.252	6.20	6.40	
H	0.030	0.033	0.75	0.85	

**Internal Structure**

Simplified Outline	Graphic Symbol
	

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7a.

## Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$T_J$	Operating Junction Temperature Range		-55		150	°C
$T_{stg}$	Storage Temperature Range		-55		150	°C
$R_{th(J-C)}$	Thermal Resistance from Junction to Case	Note 1		1.35		°C/W

## Mechanical Data

Max. Mounting Torque: 10 kg•cm

## Electrical Characteristics @ 25°C Unless Otherwise Specified(Per Diode)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage	$V_F$	$I_F=17.5A; T_J=25^\circ C$			1.2	V
Reverse Current	$I_R$	at Rated $V_R; T_J=25^\circ C$			10	uA
Junction Capacitance	$C_J$	$V_R=4V; f=1MHz; T_J=25^\circ C$		155		pF

## Curve Characteristics

Fig. 1 - Forward Current Derating Curve




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current (Per Diode)




Fig. 3 - Typical Forward Characteristics




Fig. 4 - Typical Reverse Leakage Characteristics





Fig. 5 - Typical Capacitance Characteristics



## Ordering Information

Device	Packing
SKBPC3516-BP	Bulk:50pcs/Box,400pcs/Carton

### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.