	E480232
---	----------------

Features


- Axial Lead Terminals
- High Current Transient Suppressor
- Excellent Clamping Capability
- Glass Passivated Junction
- Bi-directional
- Low Slope Resistance
- Repetition Rate(duty cycle):0.01%
- High Temperature Soldering:260°C/10 Seconds at Terminals
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant^(Note 1) ("P" Suffix Designates Compliant. See Ordering Information)

Maximum Ratings


Parameter	Symbol	Value		Unit
Operating Junction Temperature Range	T _J	-55 to +150		°C
Storage Temperature Range	T _{STG}	-55 to +150		°C
Current Rating, Rated IPP Measured With 8/20us Pulse	IPP	AK10	10	KA

1.High Temperature Solder Exemption Applied, see EU Directive Annex 7a.

Internal Structure and Marking Code

Description	Graphic symbol
Bi-directional	

AK Series TVS Diodes



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	--	0.630	--	16.00	
B	--	0.571	--	14.50	
C	0.047	0.052	1.20	1.32	
D	0.256	0.296	6.50	7.50	
E	0.922	0.979	23.43	24.87	
F	0.070	0.158	1.80	4.00	
G	0.173	0.291	4.40	7.40	-058C
	0.173	0.291	4.40	7.40	-066C
	0.206	0.325	5.25	8.25	-076C
	0.275	0.394	7.00	10.00	-170C
	0.307	0.425	7.80	10.80	-190C
	0.340	0.459	8.65	11.65	-200C
	0.340	0.459	8.65	11.65	-240C
	0.472	0.591	12.00	15.00	-380C
	0.511	0.630	13.00	16.00	-430C

Electrical Characteristics @ 25°C Unless Otherwise Specified

Part Number	Reverse Stand- Off Voltage		Breakdown Voltage		Test Current	Surge Current Rating	Maximum Clamping Voltage	Reverse Leakage	Marking
	V _{AC} (V)	V _{DC} (V)	V _{BR} (V) MIN.@IT	V _{BR} (V) MAX.@IT	I _T (mA)	8/20us (KA)	VC(V) @IPP	IR(μA) @VDC	
AK10-058C	40	58	64	70	10	10	110	20	AK10058C
AK10-066C	45	66	70	80	10	10	125	20	AK10066C
AK10-076C	54	76	83	95	10	10	135	20	AK10076C
AK10-170C	130	170	180	220	10	10	260	20	AK10170C
AK10-190C	145	190	200	245	10	10	290	20	AK10190C
AK10-200C	150	200	222	260	10	10	330	20	AK10200C
AK10-240C	180	240	250	285	10	10	340	20	AK10240C
AK10-380C	275	380	401	443	10	10	520	20	AK10380C
AK10-430C	310	430	440	490	10	10	625	20	AK10430C

Curve Characteristics

Fig. 1 - Pulse Derating Curve





Fig. 2 - Peak Pulse Power Rating Curve



Ordering Information

Device	Packing
AK10 Series	Bulk:150pcs/Box,1800pcs/Carton

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-BP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.