

Features

- Uni-Directional ESD Protection of One Line
- High Peak Pulse Current Capability
- Low Clamping Voltage
- Halogen Free. "Green" Device (Note 1)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings

- Junction Temperature Range: -40°C to +125°C
- Storage Temperature Range: -55°C to +150°C


MCC Part Number	Device Marking
ESD0751P6	7DA
ESD1051P6	aDA
ESD1251P6	cDA
ESD1551P6	fDA
ESD1851P6	iDA
ESD2451P6	oDA

IEC61000-4-2 (ESD)	Air Contact	±30KV ±30KV
IEC61000-4-4 (EFT) (5/50ns)		80A
Peak Pulse Power (8/20µs)	P _{PK}	1800W

Note :

1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

Circuit and Pin Schematic




Top View

Marking Code




ESD Protection Device

DFN1610-2



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.018	0.022	0.45	0.55	
B	0.000	0.002	0.00	0.05	
C	0.004	0.008	0.10	0.20	
D	0.062	0.066	1.55	1.65	
E	0.038	0.042	0.95	1.05	
F	0.044		1.10		TYP.
G	0.030	0.034	0.75	0.85	
H	0.006	0.010	0.15	0.25	
J	0.014	0.018	0.35	0.45	

SUGGESTED SOLDER PAD LAYOUT



Electrical Characteristics @ 25°C (Unless Otherwise Specified)
ESD0751P6

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				7	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	8		10	V
Reverse Leakage Current	I_R	$V_{RWM}=7V$			1	μA
Forward Voltage	V_F	$I_F=20mA$			1.25	V
Peak Pulse Current	I_{pp}	$t_p=8/20\mu s$			100	A
Clamping Voltage	V_C	$I_{pp}=100A, t_p=8/20\mu s$			17	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		700	900	pF

ESD1051P6

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				10	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	10.7		12.3	V
Reverse Leakage Current	I_R	$V_{RWM}=10V$			1	μA
Forward Voltage	V_F	$I_F=20mA$			1.25	V
Peak Pulse Current	I_{pp}	$t_p=8/20\mu s$			86	A
Clamping Voltage	V_C	$I_{pp}=86A, t_p=8/20\mu s$			20	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		545	650	pF

ESD1251P6

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				12	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	12.8		14.6	V
Reverse Leakage Current	I_R	$V_{RWM}=12V$			1	μA
Forward Voltage	V_F	$I_F=20mA$			1.25	V
Peak Pulse Current	I_{pp}	$t_p=8/20\mu s$			75	A
Clamping Voltage	V_C	$I_{pp}=75A, t_p=8/20\mu s$			22	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		425	510	pF

Electrical Characteristics @ 25°C (Unless Otherwise Specified)
ESD1551P6

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				15	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	15.5		18	V
Reverse Leakage Current	I_R	$V_{RWM}=15V$			1	μA
Forward Voltage	V_F	$I_F=20mA$			1.25	V
Peak Pulse Current	I_{pp}	$t_p=8/20\mu s$			60	A
Clamping Voltage	V_C	$I_{pp}=60A, t_p=8/20\mu s$			30	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		325	380	pF

ESD1851P6

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				18	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	19.2		22.5	V
Reverse Leakage Current	I_R	$V_{RWM}=18V$			1	μA
Forward Voltage	V_F	$I_F=20mA$			1.25	V
Peak Pulse Current	I_{pp}	$t_p=8/20\mu s$			50	A
Clamping Voltage	V_C	$I_{pp}=50A, t_p=8/20\mu s$			35	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		280	310	pF

ESD2451P6

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Reverse Working Voltage	V_{RWM}				24	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	24.7		29	V
Reverse Leakage Current	I_R	$V_{RWM}=24V$			1	μA
Forward Voltage	V_F	$I_F=20mA$			1.25	V
Peak Pulse Current	I_{pp}	$t_p=8/20\mu s$			40	A
Clamping Voltage	V_C	$I_{pp}=40A, t_p=8/20\mu s$			43	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$		210	250	pF

Curve Characteristics

Fig. 1 - 8 X 20µs Pulse Waveform




Fig. 2 - Non-Repetitive Peak Pulse Power




Fig. 3 - Clamping Voltage Characteristics





Fig. 4 - Pulse Derating Curve



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages. *Micro Commercial Components Corp.* products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.